

CC-122 - Contactor

Spare Part Number: CC-122

Net Weight: 0.54kg

Net Dimensions: 138.00mm x 85.00mm x 56.00mm

Technical Datasheet: [Protected Link](#)

Certification: [Protected Link - CE Declaration](#)

Description

CC-122 Contactor

A contactor is an electrically-controlled switch used for switching an electrical power circuit. A contactor is typically controlled by a circuit which has a much lower power level than the switched circuit, such as a 24-volt coil electromagnet controlling a 230-volt motor switch.

Basic Specs

Standards	IEC/EN 60947, VDE 0660, UL, CSA
Lifespan, mechanicalDC operated [Operations]	10 x 10 ⁶
Operating frequency, mechanical DC operated [Operations/h]	5000
Climatic proofing	Damp heat, constant, to IEC 60068-2-78
	Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature Open	-25 - +60 °C
Ambient temperature Enclosed	- 25 - 40 °C
Ambient temperature Storage	- 40 - 80 °C

Equipment Ref

EVO 4 DLF Ref. **K-UVA** - Contactor for UVA Lamp banks 1, 2 and 3, **K-UVC** - Contactor for UVC Lamp banks 1, 2 and 3

EVO 5 DLF Ref. **K-UVA** - Contactor for UVA Lamp banks 1, 2 and 3, **K-UVC** - Contactor for UVC Lamp banks 1, 2 and 3

EVO 5 BP Ref.

Easy to Plate EVO 5 BP D Ref.

Easy to Plate EVO 5 BP I Ref. **K_UVA** for UVA Lamps Banks 1 to 3, **K_UVC** for UVC Lamps Banks 1 to 3.

620 Ref. **KP1, KP2, KP5**

621 Ref. **KP1, KP2, KP5**

830 Ref. **KP1, KP2, KP5, AK**

810 Ref **K1**

812 Ref **K1**

Catalogues/Families

Suitable for the following equipment models:	
EASY TO PLATE EVO 5 BPI	
EVO 4 E	
EVO 4 EDLF	
EVO 4 ELF	
EVO 5 E	
EVO 5 ELF	
Spare Part Type	
Electrical Component	
Spare Part Group	
Contactor	
Stock Type	
Standard Stock	

Product Gallery

