# CC-122 - Contactor



**Product Code:** CC-122

Weight: 0.54kg

**Dimensions:** 138.00mm x 85.00mm x 56.00mm

**Technical Datasheet:** Protected Link

**Certification:** Protected Link - CE Declaration

#### **Description**

# **CC-122 Contactor**

A contactor is an electrically-controlled switch used for switching an electrical power circuit. A contactor is typically controlled by a circuit which has a much lower power level than the switched circuit, such as a 24-volt coil electromagnet controlling a 230-volt motor switch.

### **Basic Specs**

Standards IEC/EN 60947, VDE 0660, UL, CSA

Lifespan, mechanical DC operated  $10 \times 10^6$ 

[Operations]

Operating frequency, mechanical DC 5000

operated [Operations/h]

Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Open -25 - +60 °C

Ambient temperature Enclosed -25 - 40 °C

Ambient temperature Enclosed - 25 - 40 °C Ambient temperature Storage - 40 - 80 °C

<b>Equipment Ref</b> EVO 4 DLF Ref. <b>K-UVA</b> - Contactor for UVA Lamp banks 1, 2 and 3, <b>K-UVC</b> - Contactor for UVC Lamp banks 1, 2 and 3
EVO 5 DLF Ref. <b>K-UVA</b> - Contactor for UVA Lamp banks 1, 2 and 3, <b>K-UVC</b> - Contactor for UVC Lamp banks 1, 2 and 3
EVO 5 BP Ref.
Easy to Plate EVO 5 BP D Ref.

Easy to Plate EVO 5 BP I Ref. **K\_UVA** for UVA Lamps Banks 1 to 3, **K\_UVC** for UVC Lamps Banks 1 to 3.

620 Ref. **KP1, KP2, KP5** 

621 Ref. **KP1, KP2, KP5** 

830 Ref. **KP1, KP2, KP5, AK** 

810 Ref **K1** 

812 Ref **K1** 

## **Specification**

Suitable for the following ed	quipment models:
EASY TO PLATE EVO 5	
BPI	
EVO 4 E	
EVO 4 EDLF	
EVO 4 ELF	
EVO 5 E	
EVO 5 ELF	
Spare Part Type	
Electrical Component	
Spare Part Group	
Contactor	
Stock Type	
Standard Stock	

**Product Gallery** 

