

LOCTITE SI 5900 - Silicone-based gasketing



Product Code: LOCTITE SI 5900

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Technical Datasheet: [Protected Link](#) - **Safety Datasheet:** [Protected Link](#)

Description

LOCTITE SI 5900 Silicone-based gasketing

Product suitable for various substrates. Good resistance to oil and joint movement.

LOCTITE® SI 5900 is a low strength, moisture-cured, thixotropic silicone-based paste. Typical applications include stamped sheet metal covers (timing covers and oil sumps).

It exhibits a rapid skin-over time of 15 min and is suitable for gaps up to 1 mm. As a single component it requires no mixing.

- Good oil resistance
- Withstands joint movement
- Reduces migration of liquid after application
- Adheres to metal, plastic, glass and ceramic materials

Specifications

Technical Information

Color	Black
Extrusion Rate	30.0 g/min.
Key Characteristics	Oil Resistance: Excellent Oil Resistance,

Operating Temperature	Adhesion: High Adhesion
Substrates	-65.0 - 400.0 °F (-55.0 - 200.0 °C)
Tack Free Time	Metal, Plastic
	15.0 min.

Specification

Stock Type	
Made to Order	